

Appointed UK Reseller:

Visual Precis<mark>io</mark>n 🖽

2 Sycamore Tree • Elmhurst Business Park
Park Lane • Elmhurst • Lichfield • WS13 8EX • United Kingdom
Tel: +44(0)1543 262222 • Email sales@VisualPrecision.co.uk

GTCO CalComp by Turning Technologies 14557 N. 82nd Street I Scottsdale, AZ 8526

Roll-Up III™

FLEXIBLE LARGE FORMAT DIGITIZER SERIES

The affordable measuring module for architects, construction estimators, engineers and surveyors!

Transform any environment into a collaborative workspace. The Roll-Up III digitizer series offers complete mobility and is engineered with GTCO CalComp by Turning Technologies exclusive patented Redundant Grid Technology™ for greater durability and ruggedness. Simple setup makes the Roll-Up III versatile for use in the office or in the field.

Built-in USB connectivity allows power to be supplied throughthe USB port. Installation is quick and easy-WinTab applications use the Roll-Up III's plug-and-play feature and non-WinTab applications use GTCO CalComp by Turning Technologies one-step SuperSet menu. Both options allow immediate connection to a PC for use with a wide variety of applications.

Roll-Up III is available with a variety of pointing devices including a pen-shaped stylus-ideal for quantity takeoffs and the accurate 4 and 16-button MaxVu™ cursors, which feature a wide viewing area for precise digitizing.

Portable, light weight Roll-Up III digitizers are only 0.078 in / 2.0mm thick allowing them to be easily rolled for storage or transport to various task sites. Constructed with advanced materials, including a tough Lexan® work surface, Roll-Up III digitizers lay flat, maintain a smooth work surface and feature flexible dual orientation that allows the controller housing to be configured on the right or left edge of the digitizer.





FEATURES

Easy to Use

- Integrated USB connection allows digitizer to be powered through USB porton connected computer
- SuperSet[™]allowsuserstoquicklyswitchbetween applications (Serial kit required)
- Optional RS-232 serial port provides connectivity toawiderangeoflegacycomputerandoperating systems

Portable

- Extremely lightweight
- Only 0.078 in (2.0 mm) thick and easily rolled for storage or transport to various task sites
- Optional travel case available

Accurate and Flexible

- Innovative sensing technology and precision transducers provide 2,540 lpi / 100 lpmm resolution
- Dual orientation allows digitizer to be used with controller housing oriented on the right or left edge of the digitizer.

Durable and Dependable

- · State-of-the-art materials
- Durable, tough work surface
- Backed by a two-year limited U.S. warranty and free technical support



Appointed UK Reseller:

Visual Precision Ltd

2 Sycamore Tree • Elmhurst Business Park Park Lane • Elmhurst • Lichfield • WS13 8EX • United Kingdom Tel: +44(0)1543 262222 • Email sales@VisualPrecision.co.uk

GTCO CalComp by Turning Technologies 14557 N. 82nd Street I Scottsdale, AZ 8526

Technical Specificati	ons		
Platform Support	PC		
Software Drivers	Wintabcompliant, Microsoft Windows ® 7,8 and 10		
Hardware Interface	USB standard: RS-232 and QuikRuler port (requires optional power supply)		
Thickness	0.078 in/2.0mm		
RollDiameter	8 in/203 mm recommended		
Resolution	Solution Up to 2,540 lines per inch/100 lines per mm		
Proximity 0.5 in/12.7 mm			
Baud Rate	Up to 38,400		
Technology	Electrostatic (Note: for digitizing applications involving conductive inks;		
	GTCO's Super L™ Series is recommended)		
Output Formats	GTCO Type 5/5A Binary or ASCII, Summagraphics Microgrid, CalComp 9500		
Operating Modes Point, line, continuous, incremental			
Power Supply	None required when connected via USB port. When connected via serial		
	cable 120V/60 Hz standard, 100-240V/50-60 Hz optional		
Operating Temperature	40 to 115°F/5 to 46°C		
Storage Temperature	0to+150°F/-18to+66°C		
Humidity Range	0 to 90%, noncondensing		
Warranty	One-year limited warranty RTB		

Tablet	Tablet Options and Physical Dimensions				
Model	Active Area	Footprint	Weight	Average	
				Shipping Weight	
3036	30 x 36 in/762 x 914 mm	35 x 44 in/889 x 1,118 mm	6 lbs./2.7 kg	17 lbs./7.7 kg	
3648	36 x 48 in/914 x 1,219 mm	41 x 56 in/1,041 x 1,422 mm	7.25 lbs./3.3 kg	21 lbs./9.5 kg	

*NOTE: 2024 Model no longer available

Purchase Includes:	Transducer Options:	Transducer Options:
 Roll-Up III digitizer One transducer USB cable Shipping/storage tube with insert 	 Corded 16-button cursor Corded stylus with tip and 2 side switches 	 Plan hold down clamps Deluxe travel case QuikRuler LCD module Serial interface cable and power supply kit